



RYANZ INSTALLATION KIT

COMPONENTS LIST AND DESCRIPTION FOR
THE RYANZ HOT WATER INSTALLATION KIT.

07 578 9238

info@ryanzhotwater.co.nz

70 Courtney Road, Parkvale, Tauranga 3112.



ALUMINIUM DRIP TRAY

Longer Lasting. Sizes 520 -595mm.



DRIP TRAY WASTE

Stainless Steel bowl made of 302 SS.

PP Waste material.

40mm BSP waste connection thread.

Double washers.



DRAIN HOSE

20mm flexible 302 SS.
corrugated drain hose.

Connect to tundish via circlip and
connects to brass tee.

Flat high tempered washer.
3/4" female nut.




BRASS TEE

1/2" x 1/2" x 3/4" brass tee

Connection from the 3/4" drain hose
to the tundish.

Combining the 1/2" drain lines from
the TPR valve and expansion valve.



TUNDISH

RYANZ designed and NZ made.
2 piece tundish design.

Connects drip tray waste to tray and
tundish.

RYANZ threaded pin.



GALVANIZED SADDLES

Simple 22mm galvanized saddles

Hold the 3/4" drain hose to the hot
water cylinder via 3 x 1/2" drive tech
screws



FLEXI HOSES

For hot and cold connections.
Quick and easy installation.
Stainless Steel.

750mm long.

Flat high tempered washers.
Outer braided cover is 304 SS,
inner corrugated hose is 316 SS.

NOTE: There is no EPDM rubber in our
products, meaning there is no risk of
the rubber perishing and bursting in
the future.



CYLINDER RESTRAINTS

A RYANZ innovation using 25mm
cargo straps and ratchet hot water
cylinder restraints.

Holds the hot water cylinder in place to
avoid tipping and moving in the event
of an earthquake.

The only restraint on the market that
can truly put tension on the cylinder.

TRADITIONAL INSTALLATION

